

4.23.10 HARNESS REQUIREMENTS BY VEHICLE PERFORMANCE

Harness Requirements by Vehicle Performance/ Specification	
Cars slower than 12.00 seconds 1/4 mile* and Modern Street Cars slower than 10.00 seconds 1/4 mile*.	A, B, C, D, E
Cars quicker than 11.99 seconds 1/4 mile* and/or faster than 110 mph.	B, C, D, E
All Modified Eliminator cars slower than 150 mph. Cars faster than 130 mph.	C, D, E
All Rear Engine Dragsters (excluding JDs) and all Modified Eliminator cars between 150 mph and 200 mph. All cars with a known performance of faster than 200 mph.	D, E

* or equivalent.

- A: Quick Release lap sash 3-point to AS E35 or AS/NZS 2596.
- B: 4-point to AS E35 or AS/NZS 2596.
- C: 5-point to SFI 16.1 or FIA 8853.
Constructed with a minimum shoulder webbing width of 3 inches (75 mm) and a minimum of 2 inch (50 mm) wide waist and crotch webbing.
- D: Centre Locking 5-point, V type to SFI 16.1 or FIA 8853.
Minimum webbing width 3 inches (75 mm), or webbing width as per the manufacturers requirements complying with SFI 16.1 when used with an approved head/ neck restraint system.
- E: Centre Locking 5-point or 6-point, V type to SFI 16.1.

Vehicle Performance	Harness Expiry
Cars slower than 12.00 seconds (1/4 mile) or Modern Street Cars slower than 10.00 seconds (1/4 mile).	No expiry, except where harness has been used/ involved in a significant crash or has any other damage.
Cars quicker than 11.99 seconds (1/4 mile) and/or faster than 110 mph.	No expiry, except where harness has been used/ involved in a significant crash or has any other damage.
All Modified Eliminator, Supercharged Outlaws, Group 2 and 3 cars slower than 150 mph. Cars faster than 130 mph.	10 years from date of manufacture or 5 years from its use by date, whichever is sooner. When harness has been used/ involved in a significant crash or has any other damage.
All Rear Engine Dragsters (excluding Junior) and all Modified Eliminator, Supercharged Outlaws, Group 2 and 3 cars between 150 mph and 200 mph maximum speed.	10 years from date of manufacture or 5 years from its use by date, whichever is sooner. When harness has been used/ involved in a significant crash or has any other damage.
All vehicle with a known performance of 200 mph or more maximum speed.	If SFI 16.1; 3 years from date of manufacture or on expiry date, whichever is sooner. If FIA 8853-98, 5 years from date of manufacture or on expiry date, whichever is sooner.