

Chain Guard: Exposed chains or belts must be covered on the top run from the vertical centreline of the rear sprocket for the maximum allowable distance (on the swing arm). The chain guard cover must be fastened to the swing arm for both fixed and moving swing arms.

Minimum material specifications for chain guards: 25 mm (1 inch) by 3.0 mm (1/8 inch) Steel, Chromoly or Aluminium.

Flywheels: Exposed Flywheels and clutches must be adequately protected from rider contact with material that will not flex or contact clutch unit with a minimum requirement of 5.0 mm (3/16 inch) Aluminium.

Cylinder Head Restraints: NB/T must be fitted with a ballistic containment cover of metal or fabric with ballistic qualities, surrounding each cylinder head and retained by straps attached to the crankcase independently of each cylinder/ head unit or a device meeting SFI 46.1.

Brakes: Operative brakes, front and rear are required. NB/T require hydraulic type front and rear. Minimum size is 230 mm (9 inch) diameter with 3.0 mm (1/8 inch) rotor thickness.

Suspension: Front Suspension must have a minimum fork tube diameter of 30 mm (1 3/16 inch). All forks must have some form of shock dampening and rebound absorption. Fork bracing is required on all bikes known to be capable of exceeding 130 mph 1/4 mile. Steel or Steel-reinforced fibreglass front mudguards are acceptable as fork bracing.

External straps or devices used to limit the downward travel of forks permitted but must be recognisable as fit for purpose. Rear suspension optional.

Hagon type rubber band suspensions are prohibited.

Steering: Steering dampers are required.

Wheelie Bars: Permitted but are required upon testing, to be capable of supporting the weight of the bike with the rider in position.

Night Lighting: Required.

Self Starting: Required. Push starts are prohibited. Refer Support Group, Self Starting.

Licence Requirement: Group 2 UDL as a minimum.

Clothing: The wearing of club "colours" in conjunction with leathers or otherwise is expressly forbidden. Refer Protective Clothing.

Technical Inspection: Required.

