

4.23.8 HARNESS REQUIREMENTS BY VEHICLE PERFORMANCE

Harness Requirements by Vehicle Performance/ Specification	
Unmodified Modern Cars 10.000 seconds (1/4 mile)* 134.99 mph or slower. Unmodified Cars and Modified Cars 12.000 seconds (1/4 mile)* 109.99 mph or slower.	A, B, C, D
Unmodified Modern Cars 9.999 seconds (1/4 mile)* 135.00 mph - 149.99 mph. Unmodified Cars and Modified Cars 11.999 seconds (1/4 mile)* 110.00 mph - 149.99 mph. All Group 2, 3 and 4 classed cars 149.99 mph and slower.	B, C, D
All cars 150.00 mph - 199.99 mph.	C, D
All cars with a known performance of 200.00 mph and faster.	D

* or equivalent.

- A: Quick Release lap sash 3-point to AS E35 or AS/NZS 2596.
- B: 4-point to AS E35 or AS/NZS 2596.
- C: 5-point to SFI 16.1 or FIA 8853, with a minimum shoulder webbing width of 3 inches (75 mm) and minimum of 2 inch (50 mm) wide waist and crotch webbing.
- D: Centre locking 5-point, **6-point or 7-point**, V type, to SFI 16.1 or FIA 8853, **with a** minimum webbing width 3 inches (75 mm), or webbing width as per the manufacturer/certification requirements when used with **SFI 38.1 or FIA 8858 head and neck restraint system (Frontal Head Restraint (FHR) system).**

Vehicle Performance	Harness Expiry
All cars 134.99 mph and slower.	No expiry, except where harness has been used/ involved in a significant crash or has any other damage.
All cars 135.00 mph to 199.99 mph.	10 years from date of manufacture or 5 years from its use by date, whichever is sooner. Or when the harness has been used/ involved in a significant crash or has any other damage.
All cars 200.00 mph and faster.	If SFI 16.1; 3 years from date of manufacture or on expiry date, whichever is sooner. If FIA 8853, 5 years from date of manufacture or on expiry date, whichever is sooner. Or when the harness has been used/ involved in a significant crash or has any other damage.